



GB 03/4099

Rec'd PCT/PTO 22 MAR 2005

10/528744 INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 18 NOV 2003

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


W. Evans

Dated

10 November 2003

BEST AVAILABLE COPY

Patents Form 1/77

Patents Act 1977
(Rule 16)25SEP02 E750000-1 200107
P01/7700 0.00-0222166.1**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

TC-MP100082-GB

2. Patent application number

(The Patent Office will fill in this part)

0222166.1

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NMT Group Plc
New Medical House
Oakbank Park
Livingston
EH53 0TH
Scotland

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

GB

7243348002

4. Title of the invention

Needle Unit

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Lloyd Wise, McNeight & Lawrence
Regent House, Heston Lane
Stockport, Cheshire SK4 1BS

Patents ADP number (if you know it)

0001115001

8458275001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 9

Claim(s)

Abstract

Drawing(s)

2 only

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 25.09.02

Lloyd Wise, McNeight & Lawrence

12. Name and daytime telephone number of person to contact in the United Kingdom

A R Collingwood 0161 480 6394

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

- 1 -

NEEDLE UNIT

This invention relates to fluid-handling devices, in particular, hypodermic
5 syringes, and is particularly concerned with needle units adapted to be coupled to syringe
barrels from which fluid is to be dispensed via the needle.

In our prior International Patent Application No. PCT/GB02/01865, there is
disclosed a syringe comprising a barrel and a needle unit comprising a housing connected
10 or connectable at one end to a barrel, a needle-mounting hub, a biasing element arranged
to urge the hub inwardly of the barrel, and a stop element blocking inward movement of
the hub into the barrel until the hub is released from the stop element in response to a
plunger associated with the barrel reaching the final part of, or the conclusion of, its
delivery stroke to allow retraction of the needle-mounting hub into the hollow plunger.
15 Such a needle unit is referred to herein as a "needle unit as defined".

In the needle unit of International Patent Application No. PCT/GB02/01865,
the stop element includes an integral seal, in particular a lip seal, to ensure that the liquid
delivered from the barrel passes through the needle.
20

The present invention seeks to provide improvements in needle units as
defined.

According to one aspect of the present invention there is provided a syringe
25 having a needle unit as defined and in which the barrel or a part for connecting the needle
housing to the barrel is provided with a seal which contacts an outer peripheral surface of
the stop element.

- 2 -

The seal may be a lip seal which tends to deflect radially inwardly when the fluid is pressurised during the delivery stroke of the plunger.

The seal may be integral with the barrel or said connecting part.

5

The housing or the connecting part may be readily connectable to the barrel but once connected the arrangement may be such that it cannot be freed from the barrel, at least not without the application of forces substantially in excess of the force required to effect the connection to the barrel.

10

The housing or the connecting part may be designed to snap engage with the barrel.

15

According to a second aspect of the present invention there is provided a needle unit in which the stop element is arranged to snap engage within the housing to couple the needle hub to the housing and retain the biasing element in a stored energy condition.

20

The biasing element is typically a coiled compression spring which is arranged in encircling relation with the needle.

25

According to a further aspect of the present invention there is provided a needle unit as defined and a sheath for enclosing the needle, the housing including one or more openings through which the sheath and stop element can make contact so that the sheath can be used to apply axial force to the stop element without significantly stressing the coupling between the stop element and the hub.

- 3 -

This aspect of the invention is particularly advantageous where a sliding type sealing action is provided between the outer periphery of the stop element and an adjacent component. The sliding type sealing action may for example be provided by means of a lip seal on the barrel or an intermediate part for connecting the housing to the barrel.

5

In one embodiment, the housing is provided with one or more openings with which a projection or projections on the stop element snap engage and the openings are so arranged that a portion or portions of the sheath can be brought into abutment with said projection(s). In another embodiment, the projection or projections on the stop element engage with an inwardly directed rib or the like on the housing. It will be appreciated that the engagement between the stop element and the housing may be effected in other ways; for example, projections on the housing may snap engage with appropriate formations on the stop element.

15

The hub and the stop element may be formed as plastics mouldings in such a way that the stop element is axially captive with the hub, the stop element and the hub being disengaged from each other during said final part of, or at the conclusion of, the delivery stroke of the plunger to allow the biasing element to drive the needle into the hollow plunger.

20

The manner in which the stop element and the hub interact with each other, the design features and production materials for these components and the biasing element may be as disclosed in International Patent Application No. PCT/GB02/01865. Also the manner in which the plunger interacts with the stop element and the hub may be as disclosed in International Patent Application No. PCT/GB02/01865.

25

The plunger may comprise a piston member and separate hollow rod arrangement as disclosed in our UK Patent Application entitled "Prefilled Fluid Handling

- 4 -

Device" and of even date herewith, the entire disclosure of which is incorporated herein by this reference.

The invention will now be described by way of example only with reference
5 to the accompanying drawings, in which:

Figure 1 is a schematic longitudinal sectional view of one form of needle unit and part of the barrel of a hypodermic syringe in accordance with the present invention;

10

Figure 2 is a perspective cut away view of another form of needle unit shown in conjunction with the barrel of a prefilled syringe.

The various aspects of the present invention may be implemented in a fluid
15 handling device comprising a barrel for containing fluid to be delivered through a needle, a needle-mounting hub at one end of the barrel, a biasing element arranged to urge the hub inwardly of the barrel, a stop element blocking inward movement of the hub into the barrel, a hollow plunger which is movable within the barrel to deliver fluid from the barrel via the needle and is associated at its forward end with a portion which is severable in
20 response to movement of the plunger over the final part of, or at the conclusion of, its delivery stroke to allow retraction of the needle-mounting hub into the hollow plunger, the hub and the stop element being formed as plastics mouldings in such a way that the stop element is axially captive with the hub, the hub and stop element being disengaged during said final part of, or at the conclusion of, the delivery stroke of the plunger to allow the
25 biasing element to drive the needle into the hollow plunger.

Referring firstly to Figure 1, a disposable medical syringe comprises a hollow barrel 10 which accommodates a plunger 11 generally of the form disclosed in

- 5 -

International Patent Application No. PCT/GB02/01865 or PCT/GB00/04573, the plunger comprising a rim portion 13A and a blocking portion 13B. The barrel 10 is provided at its forward end with a needle unit 12 comprising a housing 14 which is coupled to the the barrel 10 by any suitable means 15 such as snap engaging formations or a screwthreaded connection which may, in each case, be irreversible so that the needle unit is permanently connected to the barrel.

A needle-mounting hub 22 is accommodated within the housing 14 and is encircled by a coiled compression spring 24 which engages at its forward end with a flange 28 of a conical section 20 of the housing and at its rear end with a radial shoulder 26 on the hub 22. The spring 24 serves to bias the hub 22 and needle 30 inwardly relative to the barrel 12 (and outwardly relative to the needle unit housing).

The hub 22 is of generally cylindrical configuration and has an axial bore for reception of the needle 30. The bore may be a throughbore and may be of tapering configuration to allow the needle to be fitted to the hub as a press-fit or by spin-welding.

Rearward movement of the hub and needle assembly (to the right as viewed in Figure 1) is prevented by a stop element in the form of a crown 34 which is carried by hub 22. The crown 34 is of generally cylindrical configuration and comprises a forward portion 36 within the housing 14 and a rearward portion 40 of tapering, e.g. generally conical, configuration. The portion 40 enters the forward end of the barrel 10 and co-operates with a lip seal 38 which flares radially inwardly and is resiliently flexible so that, on insertion of the crown portion 40, it is deflected radially outwardly so that it then bears resiliently against, and makes effective sealing engagement with, the outer peripheral surface of the crown portion 40. The lip seal 38 may be integral with the barrel which itself may be a plastics moulding.

- 6 -

The hub and crown are produced as plastics mouldings by two-shot moulding which serves to integrate the two components and render them captive with each other so that they effectively constitute a one-piece component designed to separate from each other at the interface between the hub and the crown when subjected to a predetermined forwardly directed axial force. At the interface 45 between the hub and crown, the components may have interfitting formations, e.g. mating frusto-conical surfaces, which may determine at least in part the force needed to separate the two components. Separation of the hub from the crown may be effected in the manner described in detail in International Patent Application No. PCT/GB02/01865.

The crown 34 is engaged with the housing 14 by snap engagement of laterally directed projections or latches 50 with openings 52 in the wall of the housing 14. The outer faces 54 of the projections 50 are inclined so that as the crown is inserted into the housing, the projections may ride over the inner surface of the housing and the spring outwardly to effect snap engagement. This allows the crown, hub and spring to be assembled to the housing in a simple and effective manner by pushing the assembly of crown, hub and spring (against the biasing action of the spring) into the housing until the latches 50 spring into the openings 52 and prevent return movement of the assembly.

Once the crown, hub and spring assembly has been fitted to the housing, the needle unit is fitted to the barrel. This involves pushing the crown into the barrel against the resistance created by the lip seal 38. To avoid stressing the connection between the hub and the crown at this stage with the consequent risk of prematurely freeing the hub from the crown, the force needed to properly engage the crown with the lip seal is applied along a pathway which by-passes the the hub/crown connection 45. More specifically, the force is applied directly to the crown (see arrows X) through the openings 52 by way of a sheath (not shown, but see Figure 2 which illustrates the form that the sheath may take). The

- 7 -

sheath serves to shield the needle and includes ribs arranged to contact the latches 50 via the openings 52.

After the needle unit has been assembled to the barrel and the syringe is about
5 to be used to administer an injection, the sheath is removed.

Referring now to Figure 2, the syringe shown is suitable for prefilled applications as disclosed in our UK Patent Application entitled "Prefilled Fluid Handling Device" and of even date herewith, the entire disclosure of which is incorporated herein
10 by this reference. The syringe includes a barrel 110, a piston unit 114 and a hollow rod 122 for displacing the piston member 114 towards the dispensing outlet 112 of the barrel so as to discharge a prefilled amount of drug or other component from the barrel and through the needle 120 of the needle unit 118. In Figure 2, the needle unit is shown enclosed in a sheath 160 but, in practice, the sheath is removed before the contents of the barrel are
15 discharged through the needle.

Features relating to the piston member 114, the barrel 110 and the rod 122 are described in said UK Patent Application and reference should be made thereto for specific details. Briefly, the piston member comprises a central glass blocking portion 136 received
20 in but severable or dislodgeable from a plastics rim portion 130 provided with a silicone rubber seal 138 having an integral extension 144 which overlies the forward face of the piston member to eliminate any risk of constituents of the plastics moulding contaminating the contents of the chamber 116.

25 The needle unit in Figure 2 comprises a housing 162 having a relatively narrow forwardly extending section 164 and an enlarged trailing section 166, there being openings 168 in the housing 162 at the junction between the sections 164 and 166. As in the embodiment of Figure 1, the housing 162 accommodates an assembly comprising a hub

- 8 -

169, a crown 170 and a coiled compression spring 172 which is trapped in a compressed, energy storing state between the forward end of the section 164 and a shoulder 174 on the hub 169. This assembly can be fitted to the housing in the same manner as described in connection with Figure 1, i.e. by inserting the assembly until the latches snap engage in the region of the openings 168. In this case, the snap engagement is between the latches 176 and an inwardly directed rib 178. The hub and crown are coupled together at the interface 180 in the manner previously described so that the hub can be released from the crown to allow needle retraction during the final part of or on completion of the forward stroke of the piston member 114.

10 In this embodiment, instead of providing the lip seal on the barrel (in this case, a glass barrel), the lip seal 179 (see the detail view, Figure 2A) is provided on an intermediate plastics component 182 which couples the housing 162 of the needle unit to the dispensing outlet 112. The intermediate component 182 may engage with the outlet 112 in any suitable manner, e.g snap engagement or screwthreaded connection (irreversible or otherwise). The component 182 may be fitted to the barrel outlet 112 before it is engaged with the housing 162 or it may be initially fitted to the housing 162 and then coupled to the barrel outlet 112. To ensure that the interface 180 is not stressed while effecting sliding engagement with the lip seal 179, the sheath 160 can be used to apply the necessary force directly to the crown 170 via the openings 168. To this end, the sheath is provided with internal ribs 184 which, when the sheath is fitted over the housing 162, contact the crown, e.g. the forward ends of the latches 176 at locations 186.


25 In practice, the prefilled syringe barrel will initially have a bung in its outlet 188 to retain the drug or other component within the chamber defined in the forward end of the barrel by the piston member 114. When the syringe is to be used to inject a patient, the bung is removed and the needle unit is fitted to the outlet 188 using the sheath to

- 9 -

ensure that the interface between the hub and crown is not stressed during the fitting operation.


5 Whilst endeavouring in the foregoing specification to draw attention to those features of the invention believed to be of particular importance, it should be understood that the Applicant claims protection in respect of any patentable feature or combination of features disclosed herein and/or shown in the drawings whether or not particular emphasis has been placed on such feature or features.

1/2



2/2

Fig 2



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.